



ALUMINUM ELECTROLYTIC CAPACITOR

G	S	R	2	2	0	M	1	H	D	1	1	T	A	S
SERIES		TYPE		CAPACITANCE		CAP	VOLTAGE		CASE	SIZE		SPECIAL		
				(uF)		TOL	(WV)		Φ D mm	(L mm)		REQUIREMENTS		
Series	Type Code		0.1	0R1	+5	F	4	0G	3	B	Length	Packing Type		
SM	Bulk	R	0.22	R22	-5	F	6.3	0J	4	C	05	Radial Ammo Pack		
SH	Ammo Taping		0.33	R33	+10	K	10	1A	3.2	A	07	TAF	Lead kinked tap	
GS	2.5mm	U	0.47	R47	-10	K	16	1C	5	D	11	TAS	Straight lead tap	
GH	3.5mm	V	1	1R0	+20	M	25	1E	6	W	12	Lead Cut		
LZ	5mm	T	2.2	2R2	-20	M	35	1V	6.3	E	14			
LL	Erection		3.3	3R3	+15	L	50	1H	8	F	16	Process Symbol		
ZS	Erection		4.7	4R7	-15	L	63	1J	10	G	17	C/CS	3-18 φ	
GF	Lead cut&form		10	100	+20	Q	80	1K	12	H	20	FC/FM	5-8 φ	
GZ	C Type	C	22	220	-15	Q	100	2A	13	J	21	MC	10-18 φ	
NH	H Type	H	33	330	+20	T	160	2C	16	K	25	RC	20-22 φ	
RL	S Type	S	47	470	-10	T	200	2D	18	L	26			
RT	F Type	F	100	101	+10	U	250	2E	21/22	M/N	32			
RD	E Type	E	220	221	-5	U	330	2F	25	V	36			
RH			330	331	+20	H	350	2V	30	P	40			
BD			470	471	-5	H	400	2G	35	Q	42			
RB			1000	102	+5	R	450	2W	42	R	45			
WT			2200	222	-0	R	500	2H	45	U	60			
WH			3300	332					50	S				
LP			4700	472					60	T				
LH			10000	103					63	X				
			22000	223					65	Y				
			33000	333					80	Z				
			47000	473										
			10000	104										
			220000	224										
			330000	334										