

V-CHIP ALUMINUM ELECTROLYTIC CAPACITORS


GENERAL INFORMATION FOR APPLICATION

The following precautions must be observed when using electrolytic capacitors.

1. Circuit Design

- (1) Please make sure that the environmental and mounting conditions to which the capacitor to be exposed are within the conditions specified in this catalogue.
- (2) Operating temperature and applied ripple must be within the specifications.
 - ① The capacitors shall not be used in an ambient temperature which exceeds the operating temperature specified in the specification.
 - ② Do not apply excessive current which exceeds the allowable ripple current.
- (3) Appropriate capacitors which comply with the life requirement of the products, should be selected when designing the circuit.
- (4) Aluminum electrolytic capacitors are polarized. Make sure that no reverse voltage or AC voltage is applied to the capacitors. Please use non-polarized capacitors for a circuit that can possibly see reserved polarity.
 Note: Even non-polarized capacitors cannot be used for AC voltage application.
- (5) For a circuit that repeats rapid charging/discharging of electricity, an appropriate capacitor that is capable of enduring such a condition must be used. Welding machines and photo flash are a few examples of products that contain such a circuit.
 For appropriate choice of capacitors for circuit that repeat rapid charging /discharging, please consult us.
- (6) Make sure that no excess voltage (that is higher than the rated voltage) is applied to the capacitor.
 - ① Please pay attention so that the peak voltage, which is DC voltage overlapped by ripple current, should not exceed the rated voltage.
 - ② In the case where more than two aluminum electrolytic capacitors are used in series, please make sure that applied voltage should be lower than rated voltage and the voltage should be applied to each capacitor equally using a balancing resistor in parallel with the capacitor.
- (7) Outer sleeve of the capacitor is not guaranteed as an electrical insulator. Do not use standard sleeve on a capacitor in applications that require electrical insulation. When the application requires special insulation, please contact our sales office for details.
- (8) Capacitors may fail if they are used under the following conditions:
 - ① Environmental (climatic) conditions
 - (a) Being exposed to water, high temperature & high humidity atmosphere, or condensation of moisture.
 - (b) Being exposed to oil or an atmosphere that is filled with particles of oil.
 - (c) Being exposed to salty water or an atmosphere that is filled with particles of salt.
 - (d) In an atmosphere filled with toxic gases (such as hydrogen sulfide, sulfurous acid, nitrous acid, chlorine, bromine, methyl bromide, ammonia, etc.)
 - (e) Being exposed to direct sunlight, ozone, ultraviolet ray, or radiation.
 - (f) Being exposed to acidic or alkaline solutions.
 - ② Severe vibration and physical shock conditions that exceed our specification.
 Vibration test condition:
 Vibration frequency range: 10~55~10HZ
 Sweep rate : 10~55~10HZ/minute
 Sweep method : logarithmic
 Amplitude or acceleration: 1.5mm (maximum acceleration is 10G)
 Direction of vibration : X, Y, Z direction
 Testing time : 2 hours per each direction
 Shock is not applicable normally.
 If a particular condition is required, please contact our sales office.
- (9) When designing a circuit board, please pay attention to the following:
 - ① Have the hole spacing on the P.C. board match the lead spacing of the capacitor.
 - ② There should not be any circuit pattern or circuit wire above the capacitor safety vent.
 - ③ Unless otherwise specified, following clearance should be made above the pressure relief vent.

Case Diameter	Clearance Required
φ 6.3 to 16	2mm or more
φ 18 to 35	3mm or more
φ 40 or more	5mm or more
 - ④ In case the vent side is placed toward P.C. board (such as end seal vented parts), make a corresponding hole on the P.C. board to release the gas when vent is operated. The hole should be made to match the capacitor vent position.
- (10) The main chemical solution of the electrolyte and the separator paper in the capacitor are combustible. The electrolyte is conductive. When it comes in contact with the P.C. board, there is a possibility of pattern or short circuit between the circuit pattern, which could result in smoking or fire. Do not locate any circuit pattern beneath the capacitor end seal.
- (11) Do not design a circuit board so that heat generating components are placed near an aluminum electrolytic capacitor or reverse



NOTE: All designs and specifications are for reference only and are subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.

V-CHIP ALUMINUM ELECTROLYTIC CAPACITORS

Side of P.C. board (under the capacitor).

- (12) Please refer to the recommended land size in this catalogue when you design in surface mount capacitors.
- (13) Electrical characteristics may vary depending on changes in temperature and frequency. Please consider the variation when you design circuits.
- (14) When you install more than 2 capacitors in parallel, consider the balance of current following in to the capacitor.
- (15) While mounting capacitors on double side P.C. board, the capacitors should be away from those unnecessary base plate holes and connection holes.

2. Mounting

- (1) Once a capacitor has been assembled in the set and power applied, do not attempt to re-use the capacitor in other circuits or application.
- (2) Electric potential between positive and negative terminal may exist as a result of returned electromotive force, so please discharge the capacitor using 1k Ω resistor.
- (3) Leakage current of the parts that have stored for more than 2 years may increase. When leakage current has increased, please perform a voltage treatment using a 1k Ω resistor.
- (4) Please confirm ratings and polarity before installing capacitor on the P.C. board.
- (5) Do not drop the capacitors on the floor, nor use a capacitor that was dropped.
- (6) Be careful not to deform the capacitor during installation.
- (7) Please confirm that the lead spacing of the capacitor matches the pad spacing of the P.C. board prior to installation.
- (8) Please pay attention that the clinch force is not too strong when capacitors are placed and fixed by an automatic insertion machine.
- (9) Please pay attention to the mechanical shock to the capacitor by suction nozzle of the automatic insertion machine or automatic mounted, or by product checker, or by centering mechanism.
- (10) Hand soldering:
 - ① Solder condition shall be confirmed to be within the specifications.
 - ② If it is necessary that the leads must be formed due to a mismatch of the lead space to hole space on the board, bend the lead prior to soldering without applying too much stress to the capacitor.
 - ③ If you need to remove parts which were soldered, please melt the solder enough so that stress is not applied to lead.
 - ④ Please pay attention so that solder iron does not touch any portion of capacitor body.
- (11) Flow soldering (wave solder):
 - ① Aluminum capacitor body must not be submerged into the solder bath.
 - ② Soldering condition must be confirmed to be within specification.
 - ③ Please avoid having flux adhere to any portion except the terminal.
 - ④ Please avoid contact between other components and the aluminum capacitor.
- (12) Reflow soldering (SMD only):
 - ① Please follow "Reflow Soldering Condition" in this catalogue.
 - ② When an infrared heater is used, please pay attention to the extent of heating, since the absorption rate of infrared, will vary due to difference in the color and size of the capacitor.
- (13) Do not tilt lay down or twist the capacitor body after the capacitor are soldered to the P.C. board.
- (14) Do not carry the P.C. board by grasping the soldered capacitor.
- (15) Please do not allow anything to touch the capacitor after soldering. If P.C. board are stored in stack, please make sure P.C. board or the other components do not touch the capacitor. The capacitor shall not be effected by any radiated heat from the soldered P.C. board or other components after soldering.
- (16) Cleaning
 - ① Do not clean capacitors with halogenated cleaning agent. However, if it is necessary to clean with halogenated cleaning agent, please contact our sales office.
 - ② Recommended cleaning method:
Applicable: Any type, any ratings
Cleaning agents:
Based alcohol solvent cleaning agent: Isopropyl Alcohol
Based water solvent cleaning agent:
Premium alcohol solvent type: Pine Alpha ST-100S, Techno Care FRW14~17, Sanelek B-12
Surfactant type: Clean through 750H/750L/710M
Alkaline saponification agent: Aqua cleaner 210SEP
Cleaning conditions:
Total cleaning time shall be within 5 minutes by immersion, ultrasonic or other method. Temperature of the cleaning agent shall be 60 $^{\circ}$ C or lower. After cleaning, capacitors should be dried using hot air for minimum of 10 minutes along with the P.C. board. Hot air temperature should be below the maximum operating temperature of the capacitor. Insufficient dry after water rinse may cause appearance problems, sleeve shrink, bottom-plate bulge and such.
 - ③ Avoid using ozone destructive substances for cleaning agents to concern about global environment.
- (17) Fixing Material and Coating Material
 - ① Do not use any affixing or coating materials, which contain halide substance.

NOTE: All designs and specifications are for reference only and are subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.



V-CHIP ALUMINUM ELECTROLYTIC CAPACITORS

- ② Remove flux and any contamination, which remains in the gap between the end seal and P.C. board.
- ③ Please dry the cleaning agent on the P.C. board before using affixing or coating materials.
- ④ Please do not apply any material all around the end seal when using affixing or coating materials.

There are variations of cleaning agents, fixing and coating materials, so please contact those manufactures or our sales office to make sure that the material would not cause any problems.

(18)Other

Wooden package material may be subjected to fumigation by a halogen (e.g. methyl bromide) before they are exported in order

to protect them against pests. If devices with aluminum electrolytic capacitors or capacitors themselves are fumigated or packed with the pallet that is fumigated, the capacitors may internally corrode due to the halogen contents of fumigation agents.

3. In The Equipment

- (1) Do not directly touch terminal by hand.
- (2) Do not short between terminals by conductor, nor spill conductible liquid such as alkaline or acidic solution on or near the capacitor.
- (3) Please make sure that the ambient conditions where the set is installed don't have any of the following conditions:
 - ① Where capacitors are exposed to water, high temperature & high humidity atmosphere, or condensation of moisture.
 - ② Where capacitors are exposed to oil or an atmosphere that is filled with particles of oil.
 - ③ Where capacitors are exposed to salty water, high temperature & high humidity atmosphere, or condensation of moisture.
 - ④ The atmosphere is filled with toxic acid gasses (e.g. hydrogen sulfide, sulfurous acid, nitrous acid, chlorine, bromine, methyl bromide, etc.).
 - ⑤ The atmosphere is filled with toxic alkaline gasses (e.g. ammonia).
 - ⑥ Where capacitors are exposed to acidic or alkaline solutions.
 - ⑦ Since shrinkage, bulging and/or crack could be seen on outer sleeve of capacitor when capacitors are used in atmosphere where condensation of moisture occurs, please confirm their adaptation before the use. The condensation of moisture could occur when temperature cycling test/rapid change of temperature test is performed, in this case, aforementioned sleeve problem could be seen.

4. Maintenance and Inspection

Please periodically inspect the aluminum capacitors that are installed in industrial equipment. The following items should be checked:

- (1) Appearance: Remarkable abnormality such as vent operation, leaking electrolyte etc.
- (2) Electrical characteristic: Capacitance, dielectric loss tangent, leakage current etc., which are specified in this catalogue.

5. In an Emergency

- (1) If you see smoke due to operation of safety vent, turn off the main switch or pull out the plug from the outlet.
- (2) Do not draw your face to the safety vent since gas over 100°C will be emitted when the safety vent operates. If the gas has entered your eyes, please flush your eyes immediately in pure water. If you breathed the gas immediately wash out your mouth and throat with water.
- (3) Do not ingest electrolyte. If your skin is exposed to electrolyte, please wash it away using soap and water.

6. Storage

- (1) Do not keep capacitor in high temperature and high humidity.
Storage conditions should be:

Temperature : +5°C ~ +35°C
Humidity : lower than 75%
Place : Indoor

- (2) Avoid ambient conditions where capacitors can be covered with water, brine or oil.
- (3) Avoid ambient conditions where capacitors are exposed to poisonous gases such as hydrogen sulfide, sulfurous acid, nitrous acid, chlorine, ammonium etc.
- (4) Do not keep capacitor in conditions that expose the capacitor to ozone, ultraviolet ray or radiation.
- (5) Store capacitors in a packed condition as much as possible.

7. Disposal

- (1) Please dispose capacitors in either of the following ways:
 - ① Incinerate (at a temperature of 800°C or higher) capacitors after crushing parts or making a hole on the capacitor body.
 - ② If incineration is not applicable, hand them over to a waste disposal agent and have them buried in a landfill.
- (2) When removing a capacitor from the circuit board or when disposing of capacitor, please ensure that the capacitor is properly discharged.

8. Others

- (1) The products meet or exceed quality standards specified by JIS-C-5141 and with the reliability requirements refer to JIS-C-5102.
- (2) None of ozone depleting chemicals (ODC) under the Montreal Protocol is used in our manufacturing process.

NOTE: All designs and specifications are for reference only and are subject to change without prior notice. If any doubt about safety for your application, please contact us immediately for technical assistance before purchase.